










ELESA original design CFA.

3 Type

- A** 2x2 threaded blind bores
- B** 2x2 bores for socket head cap screws
- C** 2x2 bores for countersunk screws
- D** 2x2 threaded studs
- E** 2x threaded studs
2x bores for socket head cap screw
- F** 2x threaded studs
2x bores for countersunk screws
- G** 2x threaded blind bores
2x threaded studs
- H** 2x threaded blind bores
2x bores for socket head cap screws
- I** 2x threaded blind bores
2x bores for countersunk screws



1

2

l_1	l_2	d_1	d_2	d_3	h_1	h_2	h_3	l_3	l_4	m_1 $\pm 0,25$	m_2 $\pm 0,25$	t_1	t_2
39*	40	M 4	4,3	3	14	9	9,5	-	14	25	25,1	6,5	4,5
48	49	M 5	5,5	4	19	11	13	14	17	31	30,5	7	5,5
64	65	M 6	6,5	5	23	13,5	15	18	24	40	40	10	6,5
98	98	M 10	10,5	8	35	20,5	23	20	35	63	60	15	10,5

* Size 39 only available in types A, B and C

Specification

- Plastic (Polyamide PA)
 - black, matt
 - temperature resistant up to 80 °C
- Pin
Stainless Steel AISI 303
- Threaded bushes Brass, nickel plated
- Threaded studs Brass, nickel plated
- Plastic characteristics → Page 1141
- Stainless Steel characteristics → Page 1144
- Load rating information → Page 1154
- RoHS compliant

How to order

GN 151-48-49-B

- 1** l_1
- 2** l_2
- 3** Type