

Ref. MR CI 80 UO3A - 28 x 250 - 26 B3 without motor **Technical Report 1.0**

2014.05

n. 720088

20/03/2017

Standard product: Yes

DE-17-000511/00 pos. 1

Bevel helical Gearmotor - G series

Motor catalogue TX (Frequency 50 Hz)

Application given data N.A.

MR CI 80 UO3A - 28 x 250 - 26 B3 without motor Designation:

Mounting position B3, $n_1 = 1400 \text{ [min}^{-1}\text{]}$

Accessories and special designs

Reducer/Gearmotor specifications		
Transmission ratio i		26,0
Output speed n ₂	[min ⁻¹]	53,8
Input speed n_1	[min ⁻¹]	1400
Input power P ₁	[kW]	N.A.
Output torque M ₂	[N m]	N.A.
Service factor fs		N.A.
Efficiency		0,96
Mass of gear reducer (without motor)	[kg]	25
Previsional lubricant quantity	[1]	1,3
ISO viscosity grade (T 10-40 °C)	[cSt]	220
Nominal Data Nominal input power $P_{\rm N1}$ Nominal output power $P_{\rm N2}$ Nominal output torque $M_{\rm N2}$ Maximum output torque $M_{\rm 2max}$	[kW] [kW] [N m] [N m]	3,35 3,22 572 916
Verifications Safety factor on M _{2peak} Thermal power verfication External loads verificaton		N.A. N.A. N.A.

Top view with M.P. B3



N.A: Not Applied





Ref. MR CI 80 UO3A - 28 x 250 - 26 B3 without motor **Technical Report 1.0**

n. 720088


20/03/2017

DE-17-000511/00 pos. 1

Bevel helical Gearmotor - catalogue G

Motor catalogue TX (Frequency 50 Hz)

Main Dimensions [mm] (only for standard gearbox, in case of non-standard design see the drawing on the next page)



- a) The effective dimensions of electric motor may not match with the ones stated, in case of accessories etc.: consult us in case of trouble regarding the overall dimensions;
- b) The position of motor terminal box shown in the dimensional drawing is the standard one and may not match with the really required position;
- c) In case of brake motor the dimensional drawing always shows the release lever which is supplied only on request;
- d) When offering a gearmotor without motor, motor dimensions stated in the drawing must be updated by the Customer according to the really applied motor;

Informations and warnings:

Mounting nuts: M12 UNI 5588. With screw UNI 5737, see pag. 370 Cat. G series Maximum bending moment on flange: 200 [N m]



Ref. MR CI 80 UO3A - 28 x 250 - 26 B3 without motor Technical Report 1.0

2014.05

n. 720088


20/03/2017

DE-17-000511/00 pos. 1

Bevel helical Gearmotor - catalogue G


Motor catalogue TX (Frequency 50 Hz)

Mounting position: B3



Design: UO3A

Groove side



Plugs position

SUPPLIED FILLED WITH OIL (FOR LIFE)

▼ = filler plug (in view/not in view)
⑤ = level plug (in view/not in view)
⑥ = drain plug (in view/not in view)

Standard hollow low speed shaft

