

Krautkramer Transducer Certification

Compliant to ASTM E-1065 Guidelines

Date:

2/5/2015

Product Code: Serial Number:

113-544-000 15A01NDL

Description:

PTPA--XDCR CA211A 5X.50

Test Setup--

Test Target:

1" Steel

Energy:

2

Impedance:

50

Ohms

Equipment Used:

UTA Pulser: UTA S/N:

UTA5 MM00114

UTA Cal Due Date:

9/16/2015

O-scope SN: O-scope Cal Due Date:

C024632 10/31/2015

Func. Gen.: FG Cal Due Date: 2836A11161 10/31/2015

Software:

FNT0040 Rev: H

Test Data--

Sensitivity(Abs db): Pulse Duration@-20dB: 5.13E-07

-12.20 dB

Peak Frequency:

Sec 5.00E+06 Hz

Center Frequency:


4.55E+06 Hz

% Bandwidth@-6dB:

96.0 %


Inspector:

TB



Waveform is the first Return Echo from the indicated target.

Spectrum



The accuracy of the transducer described above has been confirmed by factory standard test equipment and laboratory refernce standards traceable to the National Institute of Standards and Technology. The uncertainty factor of the block standards used does not exceed 25% of the tolerance of the characteristic being verified. This facility's Quality System is registered to ISO 9001-2008, and is compliant to MIL-STD-45662A and ANSI/NCSL Z540-1-1994.

> GE Inspection Technologies, LP 50 Industrial Park Rd. Lewistown, PA 17044 Tel.: 866.243.2638

Fax: 717.242.2606

GEInspectionTechnologies.com