

powerlube™

maxilube™



P3-01C

P3-0S2



P6-01

	powerlube®	powerlube® portable greasing system	maxilube®
Feature	complete portable grease dispensing system	complete, enclosed trolley based grease dispensing system	complete portable grease dispensing system
Pump ratio	50:1	50:1	50:1
Max pump output pressure	51 700kPa (7500psi)	51 700kPa (7500psi)	51 700kPa (7500psi)
Max gun output pressure	68 900 kPa (10 000psi)	68 900 kPa (10 000psi)	68 900 kPa (10 000psi)
Bare pump	P3001	P6001	P6001
Suited to pails	20kg	12.5 – 25kg	55kg
Hose	4m x 6mm ID delivery hose	4m x 6mm ID delivery hose	4m x 6mm ID delivery hose
Control gun	B2 Booster Gun c/w ZSB swivel	B2 Booster Gun c/w ZSB swivel	B2 Booster Gun c/w ZSB swivel
Output	460g/min	460g/min	460g/min
Airline lubricator	not required	not required	not required
Fully serviceable	■	■	■
Warranty ¹	10 years	10 years	10 years
Parts guarantee ²	10 years	10 years	10 years
Grease viscosity	up to NLGI No.2	up to NLGI No.2	up to NLGI No.2
Wetted components	zinc and hard chrome-plated carbon steel, brass, Nitrile and polyurethane rubber	zinc and hard chrome plated carbon steel, brass, Nitrile and polyurethane rubber	zinc and hard chrome plated carbon steel, brass, Nitrile and polyurethane rubber
Max air pressure	150psi	150psi	150psi
Min air pressure	60psi	60psi	60psi
Air inlet	1/4" NPT (F)	1/4" NPT (F)	1/4" NPT (F)
Pump outlet	1/4" NPT (F)	1/4" NPT (F)	1/4" NPT (F)
Min compressor size	0.08m ³ /min (3 cfm)	0.08m ³ /min (3 cfm)	0.08m ³ /min (3cfm)

Note¹ Subject to Macnaught warranty terms and conditions, see inside back cover.
 Note² Parts available for 10 years from deletion or upgrade of model.