

29 August 2019

Chart of types model A480

Item No.	Model	Uniflex™ and Ultraflex™ max. 1.100 N/mm ² / 160'000 psi				Max. Tension		Tension speed	
		Width		Thicknesses		N	lbs	mm/sec.	inch/sec.
		mm	inch	mm	inch				
13.4050	A480/10/0.38-0.63/4.5	10	3/8"	0,38-0,63	.015-.025	4.500	1,000	100	4.0
13.4052	A480/10/0.38-0.63/2.5	10	3/8"	0,38-0,63	.015-.025	2.500	560	180	7.1
13.4070	A480/13/0.38-0.63/4.5	13	1/2"	0,38-0,63	.015-.025	4.500	1,000	100	4.0
13.4072	A480/13/0.38-0.63/2.5	13	1/2"	0,38-0,63	.015-.025	2.500	560	180	7.1
13.4090	A480/16/0.38-0.63/4.5	16	5/8"	0,38-0,63	.015-.025	4.500	1,000	100	4.0
13.4092	A480/16/0.38-0.63/2.5	16	5/8"	0,38-0,63	.015-.025	2.500	560	180	7.1
13.4110	A480/19/0.38-0.63/4.5	19	3/4"	0,38-0,63	.015-.025	4.500	1,000	100	4.0
13.4112	A480/19/0.38-0.63/2.5	19	3/4"	0,38-0,63	.015-.025	2.500	560	180	7.1

Uniflex™ = Regular duty strapping max. 850 N/mm² / 123'000 psi

Ultraflex™ = High tensile strapping max. 1100 N/mm² / 160'000 psi

Accessories

A48.1304 Suspension bracket for horizontal and vertical applications

Recommended seals

Width mm	Inch	Dimensions (W, L, T) mm inch	
10	3/8"	10 x 22 x 0,6	3/8 x 7/8 x .024
13	1/2"	13 x 22 x 0,6	1/2 x 7/8 x .024
16	5/8"	16 x 22 x 0,6	5/8 x 7/8 x .024
19	3/4"	19 x 22 x 0,6	3/4 x 7/8 x .024

Tensile strength of the seal material: 600 N/mm² / 87'000 psi